Rackmount PDU with 8 Outlets and Surge Protection - 1U

Product ID: RKPW081915



This 8-outlet (120V 15A)(12A UL) Rack PDU delivers a cost-effective power distribution solution for your server rack/cabinet. The 1U PDU can be mounted horizontally in any server rack 4inin depth or greater, to provide eight 120V 15A power ports/outlets, and features a rugged steel casing to ensure maximum durability.

The front of the PDU features two LEDs to indicate proper ground and surge detection while enabling you to control the power state with an illuminated power/reset switch.

To prevent costly breakdowns of connected devices, the rackmount PDU features a built-in circuit breaker and reset switch, ensuring dependable performance of vital equipment.

Certifications, Reports and Compatibility

Applications

• 8 easily accessible power outlets in a compact 1U of rack space

• Localize the power control for all of your connected system

Features

• POWER AND CHARGE: This rack mount power strip provides an additional 8 NEMA 5-15 outlets (120V/15A) and features a 6ft (1,8m) long cord so you can plug your devices in while leaving the rack mobile

• 1U RACK DESIGN: Compatible with all 19" server racks 4 inches or deeper, this horizontal-mount power distribution unit fits many network racks and has an integrated power cord; ANSI/EIA RS-310-D standard

• EASY INSTALLATION: This IT-grade rackmount PDU features a rugged steel chassis, LED indicators for ground and surge protection, and lets you control the power state with power and reset switches

• PROTECTS YOUR EQUIPMENT: This rack mountable 8-outlet (120V) power strip features a built-in circuit breaker and reset switch, ensuring a dependable performance of your networking equipment

• THE IT PRO'S CHOICE: Designed and built for IT Professionals, this rack PDU is backed for 2-Years, including free lifetime 24/5 multi-lingual technical assistance

General		
	UPC	065030836555
	Package Quantity	1
	Warranty	2 Years
Power		
	Input Voltage	120 AC
Physical & Environmental		
	Color	Black
	Material	Steel
	Cable Length	6.0 ft [1.8 m]
	Product Length	19.0 in [48.3 cm]
	Product Width	3.8 in [95.5 mm]
	Product Height	1.7 in [42.7 mm]
	Weight of Product	4.3 lb [2.0 kg]
	Operating Temperature	-5C to 45C (23F to 113F)
	Storage Temperature	-25C to 65C (-13F to 149F)
	Humidity	5% to 95% RH non-condencing
Performance		
	Nominal Input Voltage	120V
	Nominal Output Voltage	120V

	Maximum Output Voltage	125V
	Maximum Total Current	15A
	Maximum Total Current Draw per Phase	15A
	Regulatory Derated Input Current (North America)	12A
	General Specifications	Surge Protection: 1800 Joules

Hardware

	Number of Power Outlets	8
	Rack-Mountable	Yes
	LED Indicators	1 - Ground
		1 - Surge
	Form Factor	Horizontal

Packaging & In-the-Box

	Included in Package	1 - 8 Port Power Distribution Unit
		4 - M5 Screws
		4 - M5 Cage Nuts
		1 - Installation Document
	Package Width	9.2 in [23.3 cm]
	Package Depth	20.5 in [52.1 cm]
	Package Height	2.4 in [62 mm]
	Shipping (Package) Weight	4.9 lb [2.2 kg]

Connector(s)

	Connector 1 (Quantity)	1
	Connector 1	NEMA 5-15 (125V AC, 15A)
	Connector 2 (Quantity)	8
	Connector 2	NEMA 5-15 (125V AC, 15A)

***Product appearance and specifications are subject to change without notice.**